



|                                                                                              | P4-050    | P4-100   | P4-150   | P4-200   |
|----------------------------------------------------------------------------------------------|-----------|----------|----------|----------|
| <b>Cabinet Construction</b>                                                                  |           |          |          |          |
| Base and cabinet material and thickness iaw UL-495                                           | N/A       | Standard | Standard | Standard |
| White powder-coated 16 ga galvanized steel frame                                             | N/A       | Standard | Standard | Standard |
| Galvanized steel 12 ga base & meter brackets                                                 | N/A       | Standard | Standard | Standard |
| White powder coated electronics enclosure with lexan display protection                      | Standard  | Standard | Standard | Standard |
| Stainless steel 18 ga top cap and environmental hood                                         | Standard  | Standard | Standard | Standard |
| Insulated electronics enclosure for condensation protection                                  | Standard  | Standard | Standard | Standard |
| Robust and attractive design                                                                 | Standard  | Standard | Standard | Standard |
| Injection molded nozzle boot for GasGuard GG20L autogas nozzle                               | N/A       | Standard | Standard | Standard |
| <b>Hydraulic Enclosure &amp; Assembly</b>                                                    |           |          |          |          |
| Class 1, Division 1 rated Enclosure for hydraulics                                           | Standard  | Standard | Standard | Standard |
| UL Listed components, including valves, solenoids, meter, connections, pulser, etc           | Standard  | Standard | Standard | Standard |
| Fully pressure tested, 3-step, to 350 psi                                                    | N/A       | Standard | Standard | Standard |
| Liquid and Tank vapor pressure gauges for diagnostics                                        | N/A       | Standard | Standard | Standard |
| Liquid and vapor isolation valves for ease of service                                        | N/A       | Standard | Standard | Standard |
| open and accessible for service & diagnostics                                                | Standard  | Standard | Standard | Standard |
| Class 1, Division 1 UL listed conduit, connections and appliances                            | Installer | Standard | Standard | Standard |
| Isolated solenoid flow controls on 2 hose models                                             | Option    | Standard | Standard | Standard |
| Access for installation of knock-over protection devices such as Squibb Taylor Tropod system | N/A       | Standard | Standard | Standard |
| 3/4" delivery hose for ACME nozzle hoses Recommended                                         | N/A       | Standard | Standard | Standard |
| 1/2" delivery hose for POI/QCC nozzle recommended                                            | N/A       | Standard | Standard | Standard |